

# Adestor

Vinilo de impresión monomérico brillo

## TECHNICAL SPECIFICATIONS

### Face Material

Type	Monomeric vinyl
Colour and Finish	Gloss white
Weight	134 g/m <sup>2</sup> ±10% ISO-536
Thickness	100 µ ±10% ISO 534-80

### Adhesive

Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Medium
Tack	Medium N/inch <sup>2</sup>
Final Adhesion	High N/inch

Very high cohesion. Unsuitable for apolar surfaces (like PE and PP).

### Liner

Type	One side siliconised clay coated Kraft
Colour	White
Weight	135 g/m <sup>2</sup> ±10% PP-032 - ISO 536
Thickness	145 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

### Applications

For advertising and promotional applications (outdoor and indoor posters, and signs), and for vehicle applications (flat sided including buses, trams and taxis).

### Printing Methods

Excellent print results with UV, solvent and eco-solvent ink-jet printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

36 months, under the following storage conditions:

- Temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

# Adestor

Vinilo de impresión monomérico brillo

## TECHNICAL SPECIFICATIONS

### Face Material

Type	Monomeric vinyl	
Colour and Finish	Matt white	
Weight	134 g/m <sup>2</sup> ±10%	ISO-536
Thickness	100 µ ±10%	ISO 534-80

### Adhesive

Type	Acrylic permanent
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Medium
Tack	Medium N/inch <sup>2</sup>
Final Adhesion	High N/inch

Very high cohesion. Unsuitable for apolar surfaces (like PE and PP).

### Liner

Type	One side siliconised clay coated Kraft	
Colour	White	
Weight	135 g/m <sup>2</sup> ±10%	PP-032 - ISO 536
Thickness	145 µ ±10%	ISO 534
Transparency	n.a. %	DIN 53 147-64

### Applications

For advertising and promotional applications (outdoor and indoor posters, and signs), and for vehicle applications (flat sided including buses, trams and taxis).

### Printing Methods

Excellent print results with UV, solvent and eco-solvent ink-jet printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

### Shelf life

36 months, under the following storage conditions:

- Temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.