













## MEDIATEX® Bermuda FR

	Einheit Unit	Norm Standard	Wert Value
Substrat Substrate		DIN 60001	100% Polyester 100% polyester
Bindung Weave		DIN ISO 9354	Gewebe woven fabric
Flächengewicht Weight	 g/m <sup>2</sup>	DIN EN ISO 2286-2	300 ± 15
Brandverhalten Fire retardancy		DIN 4102 B1, ÖNORM A3800, NFPA 701, CA 1237	ja yes
Tintenart Type of ink		  	alle Solventtinten, UV-härt., Latextinten* all kinds of solvent, UV-curable, latex inks*
Anwendung Application			innen, außen (kurzzeitig) indoor, outdoor (short-term)
Breite Width	 cm inch	DIN EN ISO 2286-1	max. 308 max. 121
Druckseite Print side			Breite < 3m: Druckseite außen Breite > 3m: Druckseite innen width < 3m: print side outside width > 3m: print side inside
Rollenlänge Roll length	 m		30 - 50 ± 0,5

### Anwendungen Applications



Messebau / trade show graphic  
Roll up / roll up  
Rollo, Lamelle, Flächenvorhang /  
roller, vertical, panel blinds  
Banner / banner  
Bühnendekoration / theatre, movie, backdrops  
Frontlit / frontlit

### Besonderheiten Characteristics

- höchste Druckqualität  
highest print quality
- kein Curling  
no curling
- kein Weißbruch  
no white cracking / crazing
- schmutzabweisend  
dirt-repellent
- luftdicht  
airproof
- kalt schneidbar  
trimming cold
- hohe Reißfestigkeit  
high tear resistance
- schnelle Faltenholung  
fast crease recovery

\* nicht für Außenanwendungen / not for outdoor use

All details are nominal values and are subject to change within usual tolerances (± 5%). The information provided in this document is based on current knowledge and experience. They do not exempt a manufacturer/processor from carrying out their own tests and trials as their in-house handling and manufacturing processes can have a significant range of influences on outcomes. Application, utilisation and processing of products is taking place outside of our control and are therefore the sole responsibility of the manufacturer/processor. date: 04/2019