

TerraPrint Gloss

SLIGHTLY WOOD CONTAINING FULLY COATED FINE PAPER

TerraPrint Gloss is a slightly wood containing fully coated fine paper for picture printing.

- High gloss
- Good opacity
- Excellent runnability and high yield

TYPICAL END USES

Books
Magazines
Promotional prints
Catalogues

PRINTING METHODS

Sheet fed offset, letterpress are suitable.

VARNISHING

This paper is suitable for varnishing in grammages higher than 75 g/m².

BINDING

Thread wire and adhesive binding can be used.

FINISH

Gloss

PREPRESS

Screen rulings max 80 lines/cm (200 lines/inch), with care this limits can be exceeded. AM, FM and hybrid screens can be used.

TECHNICAL SPECIFICATIONS

Substance		g/m ²	65*	70	75	80	90
Brightness	D 65/10°, ISO 2470-2	%	89	90	90	90	90
Whiteness	CIE C/2°, ISO 11476	%	94	95	95	95	95
Opacity	D65/10, ISO 2471	%	90.5	91.5	92.5	93.5	95
Gloss TAPPI 75	ISO 8254-1	%	60	60	62	63	63
Caliper	ISO 534	µm	56	60	61	65	70
Roughness	PPS 1.0, ISO 8791-4	µm	1.1	1.1	1.1	1.1	1.1

* Upon request

ENVIRONMENT

Renewable fibre
Recyclable paper
Recyclable packaging materials

CERTIFICATES

ISO 14001 (Certificate No. 87784-2010-AE-FIN-FINAS)
ISO 9001 (Certificate No. 87783-2010-AQ-FIN-FINAS)
OHSAS 18001 (Certificate No. 87785-2010-AHSO-FIN-FINAS)
German Recommendation XXXVI for contact with food
DIN EN 71 (ISEGA Certificate No. 34047 U 12)
FSC® CoC, license code FSC® C015932
PEFC™ CoC, licence code PEFC/02-31-86

PRODUCER

Kabel Mill

STORAGE AND HANDLING

- Store the paper in a humidity and temperature controlled area at 50% relative humidity and room temperature between 19°C and 23°C.
- If the paper is stored in non-air conditioned warehouse, it is absolutely necessary to allow a stabilisation period in the print room.
- Open the protective wrapping at the moment of use.