

Adestor

Vinilo de impresión monomérico opaco brillo

TECHNICAL SPECIFICATIONS

Face Material

Type	Monomeric vinyl
Colour and Finish	Gloss white
Weight	134 g/m ² ±10% ISO-536
Thickness	100 µ ±10% ISO 534-80

Adhesive

Type	Acrylic permanent grey
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Medium
Tack	Medium N/inch ²
Final Adhesion	High N/inch

Very high cohesion. Unsuitable for apolar surfaces (like PE and PP).

Liner

Type	One side siliconised clay coated Kraft
Colour and Finish	White
Weight	135 g/m ² ±10% PP-032 - ISO 536
Thickness	145 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

Applications

For advertising and promotional applications (outdoor and indoor posters, billboards and signs), and for vehicle applications (flat sided including buses, trams and taxis).

Printing Methods

Excellent print results with UV, solvent and eco-solvent ink-jet printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, under the following storage conditions:

- Temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.

Adestor

Vinilo de impresión monomérico opaco mate

TECHNICAL SPECIFICATIONS

Face Material

Type	Monomeric vinyl
Colour and Finish	Matt white
Weight	134 g/m ² ±10% ISO-536
Thickness	100 µ ±10% ISO 534-80

Adhesive

Type	Acrylic permanent grey
Min. Appl. Temp.	+10°C
Service Temp.	-30°C/+120°C
Shear	Medium
Tack	Medium N/inch ²
Final Adhesion	High N/inch

Very high cohesion. Unsuitable for apolar surfaces (like PE and PP).

Liner

Type	One side siliconised clay coated Kraft
Colour and Finish	White
Weight	135 g/m ² ±10% PP-032 - ISO 536
Thickness	145 µ ±10% ISO 534
Transparency	n.a. % DIN 53 147-64

Applications

For advertising and promotional applications (outdoor and indoor posters, billboards and signs), and for vehicle applications (flat sided including buses, trams and taxis).

Printing Methods

Excellent print results with UV, solvent and eco-solvent ink-jet printing.

Testing for suitability between media, printers and inks is always recommended prior to use.

Shelf life

36 months, under the following storage conditions:

- Temperature of 22°C ± 2°C and 50 ± 5% of Relative Humidity.
- Storage area dry and clean.
- Keep the material in the original packaging when not used in order to protect it from dust and contamination.
- Do not expose to direct sunlight or heat sources.